



BC Building Code Checklist - Part 9

Project: _____
 Civic address: _____
 Permit No.: _____ Date: _____
 CRP: _____
 Certified Professional: _____

| | | | | | | | | | |
|----------|---|--------------------------|---|------------------|---|--------------------------|--|--------------------|-----------------|
| 1 | Value of Construction: \$ _____ | | Developed Site Area: _____ m ² | | | | | | |
| 2 | BUILDING DATA: | | | | | | | | |
| | Building Area: _____ m ² | | Major Occupancy(ies): _____ | | | | | | |
| | Number of Streets: _____ | | Building Height: Storey | | | | | | |
| | Construction Type Classification: <input type="checkbox"/> COMBUSTIBLE / <input type="checkbox"/> NON-COMBUSTIBLE | | | | | | | | |
| | <input type="checkbox"/> Construction Articles/Part 3: (3.2.2...../...../.....) | | | | <input type="checkbox"/> High Building 3.2.6 | | | | |
| | <input type="checkbox"/> Fire Wall: <input type="checkbox"/> 2 h <input type="checkbox"/> / <input type="checkbox"/> 4 h <input type="checkbox"/> | | <input type="checkbox"/> Mezzanine(s) | | <input type="checkbox"/> 3.2.1.2 Horizontal Fire Separation | | | | |
| | <input type="checkbox"/> Sprinkler System | | | | <input type="checkbox"/> Standpipe System | | <input type="checkbox"/> Fire Alarm System | | |
| | Fire Resistance Rating: FLOOR: _____ hr/ MEZZ.: _____ hr/ ROOF: _____ hr/LOAD BEARING: _____ hr | | | | | | | | |
| 3 | SPATIAL SEPARATION: | | | | | | | | |
| | Wall | | | | | | | | |
| | | <i>Limiting Distance</i> | <i>Area Exposing Building Face</i> | <i>L/H Ratio</i> | <i>% Opening Actual</i> | <i>% Opening Allowed</i> | <i>Type of Construction</i> | <i>Fire Rating</i> | <i>Cladding</i> |
| | <i>North</i> | | | | | | | | |
| | <i>South</i> | | | | | | | | |
| | <i>East</i> | | | | | | | | |
| | <i>West</i> | | | | | | | | |
| | <input type="checkbox"/> Openings protected L.D. <1.2 m | | | | 9.10.14.4.2 (3.2.3.5) | | | | |
| | <input type="checkbox"/> Combustible projections 1.2 m from PL | | | | 9.10.15.5.5 (3.2.3.6.1) | | | | |
| | <input type="checkbox"/> Projecting roof soffits | | | | 9.10.14.5.11 (3.2.3.6) | | | | |
| | <input type="checkbox"/> Max. size opening L.D. <2.0 m | | | | 9.10.14.4.3 (3.2.3.1.5) | | | | |
| | <input type="checkbox"/> Spacing of openings 2 m | | | | 9.10.14.4.4 (3.2.3.1.6) | | | | |
| | <input type="checkbox"/> Exit facilities protected | | | | 3.2.3.13 | | | | |
| | <input type="checkbox"/> Wall exposed to another wall | | | | 3.2.3.14 | | | | |
| | <input type="checkbox"/> Protection of exposed soffit (if permitted by 3.2.3.6) | | | | 9.10.12.4 (3.2.3.16 / 3.2.3.6) | | | | |
| | <input type="checkbox"/> Wall exposed to adjoining roof | | | | 3.2.3.15 | | | | |
| | <input type="checkbox"/> Class A, B or C roof covering | | | | 3.1.15.2 | | | | |



| | | |
|---|---|---|
| 4 | PROVISIONS FOR FIRE FIGHTING: | |
| | <input type="checkbox"/> Access above grade / <input type="checkbox"/> Access below grade | 9.10.20.1 / 2 (3.2.5.1 / 3.2.5.2) |
| | <input type="checkbox"/> Sprinklers required / <input type="checkbox"/> Sprinkler standards | 9.10.1.3.8 (3.2.2.18 / 3.2.5.12) |
| | <input type="checkbox"/> Access route location and design | 9.10.20.3 (3.2.5.4 - 3.2.5.6) |
| | <input type="checkbox"/> Access to roof over 3 storeys | 3.2.5.3 |
| | <input type="checkbox"/> Standpipes and hose connections | 9.10.1.3.9 (3.2.5.8 - 3.2.5.11) |
| 5 | FIRE SEPARATION BETWEEN OCCUPANCIES AND TENANTS, FLOOR AREAS AND SHAFTS: | |
| | <input type="checkbox"/> Separation of major occupancies | 3.1.3.1 / Table 3.1.3.1 |
| | <input type="checkbox"/> Prohibited combination of occupancies | 3.1.3.2 |
| | <input type="checkbox"/> Fire separation between suites | 9.10.9.13 (3.3.1.1) |
| | <input type="checkbox"/> Fire separation for public corridor | 9.10.9.15 (3.3.1.4) |
| | <input type="checkbox"/> Fire separation for corridors serving an Assembly occupancy | 9.10.1.3.2 (3.3.2.6) |
| | <input type="checkbox"/> Fire separation for Residential occupancy | 9.10.9.11 (3.3.4.2) |
| | <input type="checkbox"/> Fire separation of Group A, Division 1 occupancy (OL > 200 persons) | 3.3.2.2 |
| | <input type="checkbox"/> Fire separation of roof supporting occupancy | 9.10.8.7 (3.2.2.13) |
| | <input type="checkbox"/> Walkway between buildings | 3.2.3.19 |
| | <input type="checkbox"/> Underground walkways | 3.2.3.20 |
| | <input type="checkbox"/> Fire separation of repair garages and storage garages | 9.10.9.16 / 9.10.9.17 (3.3.5.5 / 3.3.5.6) |
| | <input type="checkbox"/> Vestibules | 3.3.5.4.1 / 3.3.5.7 |
| <input type="checkbox"/> Hazardous substances | 9.10.1.3.4 (3.3.1.2 / BCFC) | |
| 6 | CONSTRUCTION OF FIRE SEPARATIONS AND CLOSURES: | |
| | <input type="checkbox"/> Basis for fire separations (Article of Appendix D, ULC/CUL/WH Listing) | 9.10.3 (3.1.7) |
| | <input type="checkbox"/> Protection of openings | 9.10.9.3 - 9.10.13 (3.1.8.1) |
| | <input type="checkbox"/> Support of fire separations | 9.10.9.8 (3.1.8.2) |
| | <input type="checkbox"/> Continuity of separations | 9.10.9.2 (3.1.8.3) |
| | <input type="checkbox"/> Fire-protection rating of closures | 3.1.8.4 / 3.1.8.10 |
| | <input type="checkbox"/> Maximum openings in firewalls | 9.10.11.3 (3.1.10.5) |
| | <input type="checkbox"/> Maximum dimensions of openings | 9.10.13.8 (3.1.8.6) |
| | <input type="checkbox"/> Self closing devices | 9.10.13.10 (3.1.8.11) |
| | <input type="checkbox"/> Latches required on swing doors | 9.10.13.9 (3.1.8.13) |



| | | | | |
|---|--|---|-------------------------------|---------|
| <input type="checkbox"/> | Wired glass and glass block in exit enclosures | 9.10.13.5 (3.1.8.16 / 3.1.8.17 / Table 3.1.8.15) | | |
| <input type="checkbox"/> | Wired glass and glass block in fire separations | 9.9.4.3 (3.1.8.14) | | |
| <input type="checkbox"/> | Temperature rise rated doors | 9.10.13.1 (3.1.8.15 / 3.1.8.17 / Table 3.1.8.15) | | |
| <input type="checkbox"/> | Fire dampers / <input type="checkbox"/> Hold-open devices | 9.10.13.11 / 13 (3.1.8.7 - 3.1.8.9 / 3.1.8.12) | | |
| 7 | EXITS: | | | |
| Occupant Load 9.9.1.3 (3.1.17.1) | | | | |
| Room | Area (m ²) | ÷ | Area/person (m ²) | = Total |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| <input type="checkbox"/> | Types of exits / <input type="checkbox"/> Minimum of 2 exits | 9.9.2.1 / 9.9.8.2 (3.4.1.4 / 3.4.2.1) | | |
| <input type="checkbox"/> | Distance between exits | 9.9.8.4 (3.4.2.3) | | |
| <input type="checkbox"/> | Travel distance and location of exits | 9.9.7.4 / 9.9.8.4 (3.4.2.4 / 3.4.2.5) | | |
| <input type="checkbox"/> | Travel distance to exit in service space maximum 50 m | 3.4.2.4.3 / 3.2.1.1.8 | | |
| <input type="checkbox"/> | Clear width of exit, corridor, stair, ramp and door | 9.9.3.2 / 9.9.3.3 (3.4.3.2 / Table 3.4.3.2.A & B) | | |
| <u>Exit capacity:</u> | | | | |
| <input type="checkbox"/> | 6.1. mm/person for: ramps ≤ 1:8, doorways, corridors and passageways | 3.4.3.2 | | |
| <input type="checkbox"/> | 9.2 mm/person for: ramps > 1:8, stairs (rise > 180 mm or run < 280 mm) | | | |
| <input type="checkbox"/> | 8 mm/person for stairs (rise ≤ 180 mm and run ≥ 280 mm) | | | |
| <input type="checkbox"/> | Exit width encroachments permitted | 9.9.5.4 - 9.9.6 / 9.8.7.6 (3.4.3.3) | | |
| <input type="checkbox"/> | Headroom | 9.9.3.4 - 9.8.2.2 / 9.8.6.4 / 9.9.6.2 (3.4.3.4) | | |
| <input type="checkbox"/> | Flame spread rating for exits | 9.10.17.1 (Table 3.1.13.2. / Table 3.1.13.7) | | |
| <input type="checkbox"/> | Fire separation of exits | 9.9.4.2 (3.4.4.1. / 3.4.4.2 / 3.4.4.3) | | |
| <input type="checkbox"/> | Integrity of exits | 3.4.4.4. | | |
| <input type="checkbox"/> | Minimum 3 risers | 9.8.3.2 (3.4.6.2 (Exception 3.3.2.14.)) | | |
| <input type="checkbox"/> | Treads and risers | Table 9.8.4.1 / Table 9.8.4.2 (3.4.6.8) | | |
| <input type="checkbox"/> | Maximum of 3.7 m per flight, except Group B2 | 9.8.3.3 (3.4.6.3) | | |
| <input type="checkbox"/> | Length and width of landing | 9.8.6.3 - Table 9.8.6.3 (3.4.6.4) | | |
| <input type="checkbox"/> | Number and height of handrails | Table 9.8.7.1 / 9.8.7.4 (3.4.6.5) | | |



| | | |
|--------------------------|---|---|
| <input type="checkbox"/> | Height of openings on guards | 9.8.8.6 (3.4.6.6) |
| <input type="checkbox"/> | Number of handrails for stairs > 1100 mm | Table 9.8.7.1 (3.4.6.5) |
| <input type="checkbox"/> | Exit signs / <input type="checkbox"/> Sign for basement stair | 9.9.11.2 / 9.9.11.3 / 9.9.11.4 (3.4.5.1. / 3.4.5.2) |
| <input type="checkbox"/> | Gradients for ramps / <input type="checkbox"/> Curved stairs | 9.8.5.4 / 9.8.4.4 / 9.8.5 (3.4.6.7 / 3.4.6.8 / 3.8.3.3) |
| <input type="checkbox"/> | Horizontal exits / <input type="checkbox"/> Exterior passageways | 9.9.2.1.3 (3.4.6.10 / 3.4.1.5 / 3.4.4.3) |
| <input type="checkbox"/> | Exit at interconnected floor spaces | 3.4.3.2.6 |
| <input type="checkbox"/> | Landings 300 mm wider and longer than door | 9.9.6.6 (3.4.6.11) |
| <input type="checkbox"/> | Door swing / <input type="checkbox"/> Sliding doors in exits | 9.9.6.4 / 5 (3.4.6.11 / 3.4.6.12 / 3.4.6.14) |
| <input type="checkbox"/> | Exit doors to be self-closing | 3.4.6.13. |
| <input type="checkbox"/> | Release hardware | 9.9.6.7 (3.4.6.16 / 3.3.2.7) |
| <input type="checkbox"/> | Doors openable from inside without key | 9.9.6.7 (3.4.6.16) |
| 8 | SAFETY REQUIREMENTS WITHIN FLOOR AREAS: | |
| <input type="checkbox"/> | Means of egress from roof and terraces | 9.9.7.1.1 (3.3.1.3.3) |
| <input type="checkbox"/> | Double doors into public corridor, exit in opposite directions | 9.9.7.2.2 (3.3.1.3.9) |
| <input type="checkbox"/> | Roof top enclosure > 200 m ² , 2 means of egress | 9.9.7.1.2 (3.3.1.3.6) |
| <input type="checkbox"/> | 2 means of egress required for service spaces greater than 200 m ² or travel distance > 25 m | 3.3.1.3.7 |
| <input type="checkbox"/> | 2 egress doorways; min. 1/3 diagonal separation | 9.9.7.4 (3.3.1.5) |
| <input type="checkbox"/> | Travel distance | 9.9.7.6 (3.3.1.6) |
| | <u>Doors in access to exit:</u> | |
| <input type="checkbox"/> | Minimum 800 mm for single leaf clear opening | 9.9.6.3 / 9.9.6.6 / 9.9.6.7 (3.3.1.13 / 3.3.3.4) |
| <input type="checkbox"/> | Minimum 800 mm for active leaf in double door | |
| <input type="checkbox"/> | Readily openable without use of keys | |
| <input type="checkbox"/> | Not open onto a step | |
| <input type="checkbox"/> | Hazardous substances | 9.10.1.3.4 (3.3.1.2 / BCFC) |
| <input type="checkbox"/> | Design of hazardous areas | 9.10.1.3.4 (3.3.6 / BCFC) |
| <input type="checkbox"/> | Door swing : Occupant load > 60 or F1 occupancy must swing in direction of exit travel | 9.9.6.5.2 (3.3.1.11) |
| <input type="checkbox"/> | Minimum width of corridor | 9.9.3.3 (3.3.1.9 / 3.3.3.3.3) |
| | <u>Capacity of access to exit:</u> | |
| <input type="checkbox"/> | Corridors, passageways, doorways, and ramps not more than 1 in 8 - 6.1 mm/person | 9.9.3 (3.3.1.17. / 3.4.3.2.(1) - 8) |
| <input type="checkbox"/> | Stairs | |
| <input type="checkbox"/> | Ramps > 1 in 8 - 9.2 mm/person | |
| <input type="checkbox"/> | B2 and B3 occupancies - 18.4 mm/person | |
| <input type="checkbox"/> | Guards at roof, shaft, balcony, etc. | 9.8.8.3 (3.3.1.18) |
| <input type="checkbox"/> | Protection of openable windows | 9.8.8.1.5 (3.3.4.8) |
| <input type="checkbox"/> | Explosion venting | 9.32.1.1.2 (3.3.1.20) |
| <input type="checkbox"/> | Flame spread rating | 9.10.3.2 (3.1.13.2 / Table 3.1.13.2. 3.1.13.11) |
| <input type="checkbox"/> | Flame spread rating in elevator cab | |



| | | |
|-----------|--|-------------------------------|
| | <input type="checkbox"/> Ventilation for commercial cooking equipment | 9.10.1.4 (3.3.1.2.2) |
| | <u>Foam plastics protection in:</u> | |
| | <input type="checkbox"/> Combustible construction | 9.10.17.10 (3.1.4.2) |
| | <input type="checkbox"/> Non-combustible construction | 9.10.6.1 (3.1.5.12) |
| | <u>Requirements by occupancy:</u> | |
| | <input type="checkbox"/> Assembly A1, A2, A3, A4 | 3.3.2. |
| | <input type="checkbox"/> Detention B1, Treatment B2, Care B3 | 3.3.3. |
| | <input type="checkbox"/> Residential C | 3.3.4. |
| | <input type="checkbox"/> Industrial F1, F2, F3 | 3.3.5. |
| 9 | LIGHTING AND EMERGENCY POWER: | |
| | <input type="checkbox"/> Lighting for exits, public corridors, and rooms | 9.9.12.2 (3.2.7.1) |
| | <input type="checkbox"/> Emergency lighting | 9.9.12.3 (3.2.7.3) |
| | <input type="checkbox"/> Emergency power for lighting | 9.9.12.3.2 / 3 (3.2.7.4) |
| | <input type="checkbox"/> Emergency power for fire alarm systems | 9.10.18.3 (3.2.7.8) |
| | <input type="checkbox"/> Emergency power for B2 occupancies | 3.2.7.6 |
| | <input type="checkbox"/> Emergency power for building services | 3.2.7.9 |
| | <input type="checkbox"/> Emergency conductor protection | 3.2.7.10 |
| 10 | FIRE ALARMS: | |
| | <input type="checkbox"/> Buildings requiring a fire alarm system | 9.10.18.2 (3.2.4.1) |
| | <input type="checkbox"/> Continuity of fire alarm systems | 9.10.18.3 (3.2.4.2) |
| | <input type="checkbox"/> Types of systems | 9.10.18.3 (3.2.4.3 / 3.2.4.4) |
| | <input type="checkbox"/> Signals to fire department | 9.10.18.3 (3.2.4.8) |
| | <input type="checkbox"/> Zoning of fire alarm systems | 9.10.18.3 (3.2.4.9) |
| | <input type="checkbox"/> Fire detectors | 9.10.18.4 (3.2.4.11) |
| | <input type="checkbox"/> Smoke detectors | 9.10.18.3 (3.2.4.12) |
| | <input type="checkbox"/> Sprinkler system monitoring | 9.10.18.3 (3.2.4.16) |
| | <input type="checkbox"/> Manual pull stations | 9.10.18.3 (3.2.4.17) |
| | <input type="checkbox"/> Smoke alarms | 9.10.19 (3.2.4.21) |
| 11 | REQUIREMENTS FOR MEZZANINES AND INTERCONNECTED FLOOR SPACES: | |
| | <input type="checkbox"/> 10% mezzanine (not a storey) <input type="checkbox"/> 40% mezzanine (not a storey) | 9.3.2.1.1 (3.2.1.1) |
| | <input type="checkbox"/> Termination of vertical fire separation | 9.10.12.1 (3.2.8.1) |
| | <input type="checkbox"/> Mezzanine egress | 9.9.8.6 (3.4.2.2) |
| | <input type="checkbox"/> Interconnected floor space not permitted in B2 occup. | 9.10.9.5 (3.2.8.1) |
| | <input type="checkbox"/> Openings through horizontal fire separation for vehicular ramps in storage garage | 3.2.8.2.2 |



| | | |
|-----------|---|------------------------------------|
| | <input type="checkbox"/> Openings in fire separation for manufacturing process | 3.2.8.2.3 |
| | <input type="checkbox"/> Openings for stairways, escalators, moving walkways | 3.2.8.2.5/6 |
| | <input type="checkbox"/> Interconnected first floor and floor below or above | 9.10.9.5 (3.2.8.2.6) |
| | <input type="checkbox"/> Construction of interconnected floor space non-comb. | 9.10.9.5 (3.2.8.3) |
| | <input type="checkbox"/> Exit requirements | 9.9.3 (3.4.3.2.6) |
| | <input type="checkbox"/> Elevator openings | 3.2.8.5.3 |
| | <input type="checkbox"/> Sprinkler system / <input type="checkbox"/> Draft stops / <input type="checkbox"/> Smoke control | 3.2.8.4 / 3.2.8.7 / 3.2.8.8 |
| 12 | SERVICE FACILITIES: | |
| | <input type="checkbox"/> No storage in services spaces | 3.6.1.3 |
| | <input type="checkbox"/> Fire separation of service rooms | 9.10.10.3 (3.6.2.1) |
| | <input type="checkbox"/> No boiler under exit / <input type="checkbox"/> Door swing | 9.9.5.8 (3.6.2.2 / 3.6.2.6) |
| | <input type="checkbox"/> Fire separation of janitor rooms | 3.3.1.21 |
| | <input type="checkbox"/> Fire separation of laundry rooms | 3.3.1.22 |
| | <input type="checkbox"/> Fire separation and sprinklers for residential storage rooms | 9.10.10.6 (3.3.4.3) |
| | <input type="checkbox"/> Fire separation of electrical equipment vaults | 3.6.2.7 |
| | <input type="checkbox"/> Fire separation for elevator shafts | 3.5.3.1 / Table 3.5.3.1 |
| | <input type="checkbox"/> Fire separation for vertical services spaces | 3.6.3.1 / Table 3.6.3.1 |
| | <input type="checkbox"/> Fire separation at top/bottom of vertical service space | 3.6.3.1 |
| | <input type="checkbox"/> Fire separation of horizontal service spaces | 3.6.4.2 |
| | <input type="checkbox"/> Fire separation of fuel fired service | 9.10.10.4 / 5 (3.6.2.1) |
| | <input type="checkbox"/> Fire separation and sprinklers for garbage rooms | 9.10.10.6 (3.6.2.5) |
| | <input type="checkbox"/> Linen and garbage chutes and rooms | 9.10.10.6 (3.6.3.3) |
| | <input type="checkbox"/> Negative pressure required for vertical service space | 9.10.9.18.1 (3.6.3.4) |
| | <input type="checkbox"/> Ceiling spaces used as plenums | 9.13.1.3 (3.6.4.3) |
| | <input type="checkbox"/> Ceiling panels – hold-down clips | 9.10.3.4 (3.6.4.3) |
| | <input type="checkbox"/> Access to attic or roof space | 9.19.2.1 (3.6.4.4) |
| | <input type="checkbox"/> Access to horizontal service space | 3.6.4.5 |
| | <input type="checkbox"/> Access to crawl space | 9.18.2 (3.6.4.6) |
| 13 | HEALTH REQUIREMENTS: | |
| | <input type="checkbox"/> Height in sleeping rooms | Table 9.5.3.1 (3.7.1.1 / 9.5.3) |
| | <input type="checkbox"/> Room ventilation | 9.32 (6.2.2.1 / 6.2.2.2) |
| | <input type="checkbox"/> Medical gas piping systems | 9.31.1.1.3 (3.7.3.1 / CSA Z7396.1) |



| Plumbing Facilities 3.7.2.: | | | |
|--|---|-------------------------------|-----------------------------|
| Occupancy | # of persons of each sex | # of water closets required | # of water closets provided |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| 14 | REQUIREMENTS FOR ACCESSIBILITY : | | |
| <u>When required:</u> | | | |
| <input type="checkbox"/> New buildings – not required in: Group C occupancy, Group F1 occupancy, Group E < 50 m ² , certain 2-storey buildings with max. 600 m ² above or below first storey | | 9.5.2.1 (3.8.2.1) | |
| <input type="checkbox"/> Areas requiring barrier-free path of travel | | 3.8.3.1 | |
| <input type="checkbox"/> Existing buildings | | 3.8.4.1 | |
| <input type="checkbox"/> Main entrances | | 9.5.2.1 (3.8.3.5) | |
| <input type="checkbox"/> Width of path of travel – minimum 1500 mm | | 9.5.2.1 (3.8.3.2) | |
| <input type="checkbox"/> Ground and floor surfaces | | 9.5.2.1 (3.8.3.2) | |
| <input type="checkbox"/> Viewing positions | | 9.5.2.1 (3.8.3.15) | |
| <u>Parking:</u> | | | |
| <input type="checkbox"/> Access to parking areas | | 9.5.2.1 (3.8.2.3 / 3.8.2.38) | |
| <input type="checkbox"/> Number of stalls required | | 9.5.2.1 (3.8.3.4) | |
| <input type="checkbox"/> 3.7 m wide | | 9.5.2.1 (3.8.3.4) | |
| <input type="checkbox"/> Identification required | | 9.5.2.1 (3.8.3.4) | |
| <input type="checkbox"/> Surface treatment | | 9.5.2.1 (3.8.3.4) | |
| <u>Accessible washrooms:</u> | | | |
| <input type="checkbox"/> Where required | | 9.5.2.1 (3.8.2.3) | |
| <input type="checkbox"/> Water closet stalls min. 1500 mm x 1500 mm | | 9.5.2.1 (3.7.2.10.2) | |
| <input type="checkbox"/> Door min. 800 mm clear opening accessories | | 9.5.2.1 (3.7.2.10.2) | |
| <input type="checkbox"/> Water closets | | 9.5.2.1 (3.7.2.10.3) | |
| <input type="checkbox"/> Location of urinals | | 9.5.2.1 (3.7.2.10.6) | |
| <input type="checkbox"/> Grab bars, wash basins, mirrors | | 9.31.2.3 (3.7.2.10.4 / 5 / 7) | |
| <input type="checkbox"/> Universal toilet rooms | | 9.5.2.1 (3.7.2.10.9) | |
| <input type="checkbox"/> Bathtubs / <input type="checkbox"/> Showers | | 9.5.2.1 (3.7.2.10.10 / 11) | |
| <input type="checkbox"/> Doors and vestibules in barrier-free path | | 9.5.2.1 (3.3.1.13) | |
| <input type="checkbox"/> Power doors in hotels, B2, B3, A, D, or E > 500 m ² | | 9.5.2.1 (3.8.3.5.4) | |
| <u>Ramps:</u> | | 9.8.5.1.2 (3.8.3.3) | |

