

# District of Peachland Annual Drinking Water Report – 2019



#### **INTRODUCTION**

The District of Peachland is legally required by the *Drinking Water Protection Act* to provide an annual report on their water supply systems. The annual report will provide water system users with an overview of the system, a summary of all water tests performed and an update to any maintenance and/or improvements made to the system.

Facility Name/Number: District of Peachland Water Distribution System (#561) EOCP Classification: Level III

Facility Name/Number: Peachland Creek Water Treatment Facility (#2288)

**EOCP Classification: Level II** 

Facility Name/Number: Trepanier Creek Water Treatment Facility (#2289)

**EOCP Classification: Level II** 

Facility Name/Number: Okanagan Lake Pumps Water Treatment Facility (#2290)

**EOCP Classification: Level II** 

#### **WATER SOURCES**

Water for the District of Peachland is supplied from three surface water sources;

- Peachland Creek
- Trepanier Creek
- Okanagan Lake

The Peachland Creek system supplies water to all properties accessed from Princeton Avenue. It also supplies the properties accessed from Ponderosa Drive and the downtown area as far north as 11<sup>th</sup> Street (approximately). The Trepanier system supplies water to the remainder of the properties in the District (from 11<sup>th</sup> Street north). When the Okanagan Lake pumps are operated in place of the Trepanier Creek Intake, the supply area is identical to the Trepanier system.

The majority of water is supplied from the Peachland Creek (PCI) system (approximately 2/3) with the remainder supplied by the Trepanier Creek (TCI) system (approximately 1/3) or the Okanagan Lake Pumps. The Okanagan Lake Pumps (LPH) are typically operated during spring freshet/runoff to supply less turbid water to the Trepanier system. In 2019, the Okanagan Lake Pumps were active from May 9 – May 28 (spring freshet).

#### **DISTRIBUTION SYSTEM**

The District of Peachland currently uses chlorine gas as its primary disinfectant. Chlorine is injected using flow paced technology and is dosed to provide inactivation of bacteria, viruses and protozoan cysts which may be present within the surface water source. District staff maintain a first user residual ranging from 0.9 - 1.9 mg/L (depending on the time of year and clarity of the raw water). At the ends of the system, a chlorine residual target is set at 0.2 mg/L. A residual of chlorine remaining in the distribution system extends a measure of protection against any possible contamination entering the system after initial disinfection.

The distribution system and supply includes:

- 16 pressure reducing stations,
- 1 very high consequence dam (Peachland Lake)
- 1 high consequence dam (Silver Lake)
- 1 significant consequence dam (Glen Lake)
- 4 active reservoirs
- 6 active pump stations
- Approximately 81 km of pipeline

The Water Department is staffed by operators certified through the Environmental Operators Certification Program (EOCP – the association responsible for certification of system operators and classification of water distribution and treatment systems within British Columbia), with their certifications noted below;

- Director of Operations: Water Distribution Level IV / Water Treatment Level II
- Water Mechanic: Water Distribution Level II / Water Treatment Level II
- Water Mechanic: Water Distribution Level I

These operators have the capability to monitor the system at all times (24 hours per day, 365 days per year) through the use of the SCADA system (supervisory control and data acquisition). The system is set to alarm if it drifts beyond pre-determined set points, calling the standby operator to alert them. There is an operator on standby at all times.

#### **ROUTINE MAINTENANCE**

#### Fire Hydrants

All municipally owned fire hydrants are inspected, pressure tested and flushed annually. Hydrants undergo a complete tear down and rebuild on an as-needed basis.

#### Main Valve Exercising

Main valves are exercised at least biennially or on an as-needed basis.

#### System Flushing

System flushing occurs annually during the fall. Hydrants and blowoffs are used to pass higher velocity water through the system in order to scour any sediment that may have settled in the system over the year.

Pressure Reducing Valves (PRVs)

PRV's are inspected monthly and repaired or rebuilt on an as-needed basis.

## **WATER MASTER PLAN**

In 2007, the sitting mayor and council adopted the Water Master Plan (WMP), a set of comprehensive upgrades that was anticipated to provide treated water to Peachland in its entirety by the years 2023/24. The WMP was amended in 2015 to include information on increased population growth and changes in drinking water legislation. If more in-depth information is desired, it is available at the District's website (<a href="http://www.peachland.ca/water-master-plan-2015">http://www.peachland.ca/water-master-plan-2015</a>)

This year saw construction beginning on the new Peachland Creek Water Treatment Plant (WTP). Maple Reinders, a company well known for successfully completing similar projects, was awarded the contract and they began breaking ground in early 2019. The new plant will be capable of a daily capacity of 25 MLD (expandable to 50 MLD) and include a 2500 m³ treated water reservoir. The treatment process consists of clarification through the dissolved air flotation (DAF) process, multi-media filtration, ultraviolet (UV) disinfection and chlorination. In consultation with the EOCP, the plant has been pre-classified as a Level IV facility. Over the course of the year, the majority of concrete work was completed for the WTP and the upper reservoir. Work continues on schedule and the plant is anticipated to be nominally complete by late 2020.

Completion of the WTP will allow the District to exceed the minimum requirements of the Drinking Water Treatment Objectives for Surface Water Supplies in British Columbia. If minimum requirements are not met, water users can potentially be at increased risk of illness from protozoan pathogens.

To provide this treated water to the entire District a second project was added to the scope of construction; the installation of a large diameter water main to interconnect the Peachland Creek and Trepanier Creek systems. Over the course of 2019, the project moved forward through the completion of preliminary plans and acquisition of various statutory right-of-ways (SRW's). This project is also due to be completed by late 2020.

A summary of the anticipated project costs is noted below;

	Total Cost	Grant	Borrowing	Reserves
Water Treatment Plant	\$24 Million	\$6.9	\$9.2	\$7.9
Water Treatment Plant	\$24 WIIIION	Million	Million	Million
Transpier Interconnect	\$4.9	\$4.9		
Trepanier Interconnect	Million	Million		

## WATER SAMPLING

Drinking water samples are tested weekly for *E.Coli* and total coliforms by Caro Analytical Services in Kelowna. There were no positive bacteriological samples detected in 2019.

District employees monitor and record daily turbidity values along with pH and chlorine levels. Turbidity is one of the main parameters leading to a water quality advisory or a boil water notice. As the turbidity increases over 1 NTU, a water quality advisory is instituted. Similarly, as it increases over 5 NTU, a boil water notice is instituted. For ease of understanding and communication, if one of the sources exceeds the noted thresholds, the entire system is placed on an advisory/notice. Turbidity can affect the number and type of microorganisms that enter a surface water source. As surface waters experience increased flows (ie. spring runoff, major rainfall events, etc), turbidity can fluctuate dramatically and the public is notified accordingly. Records of average daily turbidity values can be found in Appendix IV.

Chlorine concentrations are continuously monitored at 4-5 stations throughout the system (depending on the time of year) as well as daily grab samples at a number of locations to ensure instrument accuracy, allowing CT values to be monitored.

Raw source water samples are also collected annually in order to perform a comprehensive analysis, giving an indication of any changes occurring within the water supplies. It should be noted that all raw sources tested are within the maximum allowable concentration (MAC) limits set out in the Guidelines for Canadian Drinking Water Quality. Lastly, trihalomethanes (THM`s) are also tested annually to provide an indication of the level of disinfection by-products present in the water supply system. The results from the comprehensive and THM analyses are included in Appendices I and II, respectively. The result sheets also indicate the limits or guidelines for each parameter listed.

## WATER QUALITY ADVISORIES / BOIL WATER NOTICES / DO NOT USE NOTICE

Water quality advisories and boil water notices are notifications designed to inform the public of possible public health threats. The decision to institute an advisory or notice is made in discussion with staff at the Interior Health Authority (IHA).

A <u>water quality advisory</u> (WQA) is the lowest-level notification and used in situations where the possible public health threat is modest. These advisories are instituted when the turbidity in the water source increases over a value of 1 NTU (nephelometric turbidity units). Details of WQA's issued over the past year are noted below.

A <u>boil water notice</u> (BWN) is a moderate-level notification used in situations where the possible public health threat is one that can be effectively addressed by boiling the water. These notices are typically instituted when the water source turbidity increases over 5 NTU or there is a failure in the disinfection system. Details of BWN's issued over the past year are noted below.

A <u>do not use notice</u> is the highest level of notification. It is used in situations where a significant public health threat exists (ie. Chemical spill, etc). There were no do not use notices issued in 2019.

April 10/19 - with turbidity increasing above 1 NTU, a WQA was implemented.

April 24/19 - a BWN was implemented in response to a chlorination system failure

April 29/19 - following system sampling and in consultation with IHA, the BWN was

downgraded to a WQA

May 24/19 - with turbidity decreasing below 1 NTU, the WQA was rescinded.

#### WATER CONSUMPTION

In 2019, there was a total of 2,273.22 ML passing through the District Intakes. A monthly summary of consumption per intake and a graphical percentage comparison is located in Appendix III.

#### WORKS COMPLETED AND IN PROGRESS

- Dam safety reviews and updates on the Peachland and Silver Lake dams
- Leak detection program
- Installation of new 1 ½-inch main valve, water main, and curbstops on Eyre Rd, replacing leaking galvanized line
- Water meter, pit installations.
- Trepanier Interconnect project initiated. Preliminary plans completed and reviewed and began process of acquiring necessary SRW's to facilitate construction
- Construction of the water treatment plant began. Some of the more pertinent items are listed below;
  - Maple Reinders and sub-contractors broke ground on new WTP
  - Substantial completion of 2500 m<sup>3</sup> reservoir
  - Completion of headwall and culverting of Spring Creek
  - Commenced work on subterranean level of WTP
  - Forming, pouring, and waterproofing outer walls.
  - Pouring clarified water channel and filter gallery walls
  - Pouring DAF and Floc tank walls
  - Forming footings for Chemical room and backwash channel

## Appendix I – Comprehensive Analyses (Peachland Creek Intake, Trepanier Creek Intake)





Peachland, Corporation of the District of REPORTED TO

5806 Beach Avenue

PEACHLAND, BC V0H 1X7

ATTENTION WORK ORDER N000568 Shawn Grundy

PO NUMBER

RECEIVED / TEMP 2019-10-29 12:55 / 7°C PROJECT General Potability REPORTED 2019-11-29 11:47

PROJECT INFO COC NUMBER B78229

#### Introduction:

CARO Analytical Services is a testing laboratory full of smart, engaged scientists driven to make the world a safer and healthier place. Through our clients' projects we become an essential element for a better world. We employ methods conducted in accordance with recognized professional standards using accepted testing methodologies and quality control efforts. CARO is accredited by the Canadian Association for Laboratories Accreditation (CALA) to ISO 17025:2005 for specific tests listed in the scope of accreditation approved by CALA.

Bia Picture Sidekicks



We've Got Chemistry



Ahead of the Curve



You know that the sample you collected after snowshoeing to site, digging 5 meters, and racing to get it on a plane so you can submit it to the lab for time sensitive results needed to make important and expensive decisions (whew) is VERY important. We know that too.

It's simple. We figure the more you enjoy working with our fun and engaged team members; the more likely you are to give us continued opportunities to support you.

Through research, regulation knowledge, and instrumentation, are your analytical centre for the technical knowledge you need, BEFORE you need it, so you can stay up to date and in the know.

If you have any questions or concerns, please contact me at teamcaro@caro.ca

Authorized By:

Team CARO Client Service Representative

1-888-311-8846 | www.caro.ca

#110 4011 Viking Way Richmond, BC V6V 2K9 | #102 3677 Highway 97N Kelowna, BC V1X 5C3 | 17225 109 Avenue Edmonton, AB T5S 1H7



## **TEST RESULTS**

REPORTED TO	Peachland, Corporation of the District of	WORK ORDER	N000568
PROJECT	General Potability	REPORTED	2019-11-29 11:47

Analyte	Result	Guideline	RL	Units	Analyzed	Qualifier
Trepanier Creek - Raw (Weir Block)	(N000568-01)   Matrix:	Water   Sampled: 2	2019-10-29 07	7:45		
Anions						
Chloride	2.56	AO ≤ 250	0.10	mg/L	2019-10-30	
Fluoride	0.12	MAC = 1.5	0.10	mg/L	2019-10-30	
Nitrate (as N)	< 0.010	MAC = 10	0.010	mg/L	2019-10-30	
Nitrite (as N)	< 0.010	MAC = 1	0.010	mg/L	2019-10-30	
Sulfate	13.6	AO ≤ 500	1.0	mg/L	2019-10-30	
Calculated Parameters						
Total Trihalomethanes	0.0926	MAC = 0.1	0.00400	ma/L	N/A	
Hardness, Total (as CaCO3)	113	None Required	0.500		N/A	
Langelier Index	0.2	N/A	-5.0		2019-11-13	
Solids, Total Dissolved	64.6	AO ≤ 500	1.00	mg/L	N/A	
General Parameters				7		
Colour, True	6.4	AO ≤ 15	5.0	CU	2019-11-08	HT1
Conductivity (EC)	221	N/A	2.0	μS/cm	2019-11-04	
Cyanide, Total	< 0.0020	MAC = 0.2	0.0020	mg/L	2019-11-04	
pH	7.92	7.0-10.5	0.10	pH units	2019-11-04	HT2
Turbidity	0.30	OG < 1	0.10	NTU	2019-10-30	
Microbiological Parameters						
Coliforms, Total	84	MAC = 0	1	CFU/100 mL	2019-10-30	
Background Colonies	> 200	N/A	200	CFU/100 mL	2019-10-30	
E. coli	11	MAC = 0	1	CFU/100 mL	2019-10-30	
Total Metals						
Aluminum, total	0.0120	OG < 0.1	0.0050	mg/L	2019-11-02	
Antimony, total	< 0.00020	MAC = 0.006	0.00020	mg/L	2019-11-02	
Arsenic, total	0.00065	MAC = 0.01	0.00050	mg/L	2019-11-02	
Barium, total	0.0249	MAC = 1	0.0050	mg/L	2019-11-02	
Boron, total	0.0097	MAC = 5	0.0050	mg/L	2019-11-02	
Cadmium, total	0.000013	MAC = 0.005	0.000010	mg/L	2019-11-02	
Calcium, total	36.7	None Required	0.20	mg/L	2019-11-02	
Chromium, total	< 0.00050	MAC = 0.05	0.00050	mg/L	2019-11-02	
Cobalt, total	< 0.00010	N/A	0.00010	mg/L	2019-11-02	
Copper, total	0.00129	MAC = 2	0.00040	mg/L	2019-11-02	
Iron, total	0.039	AO ≤ 0.3	0.010	mg/L	2019-11-02	
Lead, total	< 0.00020	MAC = 0.005	0.00020	mg/L	2019-11-02	
Magnesium, total	5.12	None Required	0.010	mg/L	2019-11-02	
Manganese, total	0.00732	MAC = 0.12	0.00020	mg/L	2019-11-02	
Mercury, total	< 0.000040	MAC = 0.001	0.000040	mg/L	2019-11-02	CT5
Molybdenum, total	0.0117	N/A	0.00010	mg/L	2019-11-02	
Nickel, total	< 0.00040	N/A	0.00040	mg/L	2019-11-02	
Potassium, total	1.68	N/A	0.10	mg/L	2019-11-02	
Selenium, total	< 0.00050	MAC = 0.05	0.00050	mg/L	2019-11-02	





REPORTED TO Peachland, Corporat PROJECT General Potability	ion of the District of			WORK ORDER REPORTED	N000568 2019-11-2	9 11:47
Analyte	Result	Guideline	RL	Units	Analyzed	Qualifie
Trepanier Creek - Raw (Weir Block) (NO	000568-01)   Matrix:	Water   Sampled: 2	019-10-29 07	:45, Continued		
Total Metals, Continued						
Sodium, total	4.92	AO ≤ 200	0.10	mg/L	2019-11-02	
Strontium, total	0.258	7	0.0010		2019-11-02	
Uranium, total	0.00146	MAC = 0.02	0.000020		2019-11-02	
Zinc, total	< 0.0040	AO ≤ 5	0.0040	mg/L	2019-11-02	
Volatile Organic Compounds (VOC)	***************************************	600000		LEWER I.E.		
Bromodichloromethane	0.0046	N/A	0.0010	ma/l	2019-11-08	
Bromoform	< 0.0010	N/A	0.0010		2019-11-08	
Chloroform	0.0880	N/A	0.0010	700	2019-11-08	
Dibromochloromethane	< 0.0010	N/A	0.0010	0.0000	2019-11-08	
Surrogate: Toluene-d8	96	.1305	70-130	%	2019-11-08	
Surrogate: 4-Bromofluorobenzene	63		70-130	%	2019-11-08	S02
Peachland Creek - Raw (Gabion) (N000	9568-02)   Matrix: Wa	ater   Sampled: 201	9-10-29 08:0	0		
Anions						
Chloride	26.9	AO ≤ 250	0.10	mg/L	2019-10-30	
Fluoride	< 0.10	MAC = 1.5	0.10	mg/L	2019-10-30	
Nitrate (as N)	< 0.010	MAC = 10	0.010	mg/L	2019-10-30	
Nitrite (as N)	< 0.010	MAC = 1	0.010	mg/L	2019-10-30	
					2010 10 00	
Sulfate	17.9	AO ≤ 500		mg/L	2019-10-30	
- Company	17.9	AO ≤ 500		mg/L	STATE OF THE PARTY	
- Company	0.0732	AO ≤ 500 MAC = 0.1		- C C C C C C C C.	STATE OF THE PARTY	
Calculated Parameters	petrocaria		1.0	mg/L	2019-10-30	
Calculated Parameters Total Trihalomethanes	0.0732	MAC = 0.1	0.00400	mg/L	2019-10-30 N/A	
Calculated Parameters Total Trihalomethanes Hardness, Total (as CaCO3)	0.0732 119	MAC = 0.1 None Required	0.00400 0.500 -5.0	mg/L	2019-10-30 N/A N/A	
Calculated Parameters Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved	0.0732 119 0.2	MAC = 0.1 None Required N/A	0.00400 0.500 -5.0	mg/L mg/L	N/A N/A N/A 2019-11-13	
Calculated Parameters Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved	0.0732 119 0.2	MAC = 0.1 None Required N/A	0.00400 0.500 -5.0 1.00	mg/L mg/L	N/A N/A N/A 2019-11-13	HT1
Calculated Parameters Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved General Parameters Colour, True	0.0732 119 0.2 101	MAC = 0.1 None Required N/A AO ≤ 500	0.00400 0.500 -5.0 1.00	mg/L mg/L mg/L	N/A N/A N/A 2019-11-13 N/A	НТ1
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC)	0.0732 119 0.2 101 < 5.0 266	MAC = 0.1 None Required N/A AO ≤ 500 AO ≤ 15 N/A	0.00400 0.500 -5.0 1.00	mg/L mg/L mg/L CU µS/cm	2019-10-30 N/A N/A 2019-11-13 N/A 2019-11-08 2019-11-04	НТ1
Calculated Parameters Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved General Parameters Colour, True Conductivity (EC) Cyanide, Total	0.0732 119 0.2 101	MAC = 0.1 None Required N/A AO ≤ 500	1.0 0.00400 0.500 -5.0 1.00 5.0 2.0	mg/L mg/L  CU  µS/cm mg/L	2019-10-30 N/A N/A 2019-11-13 N/A 2019-11-08	HT1
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90	MAC = 0.1 None Required N/A AO ≤ 500 AO ≤ 15 N/A MAC = 0.2 7.0-10.5	1.0 0.00400 0.500 -5.0 1.00 5.0 2.0 0.0020 0.10	mg/L mg/L  CU  µS/cm mg/L  pH units	2019-10-30  N/A  N/A  2019-11-13  N/A  2019-11-08  2019-11-04  2019-11-04  2019-11-04	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity	0.0732 119 0.2 101 < 5.0 266 < 0.0020	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2	1.0 0.00400 0.500 -5.0 1.00 5.0 2.0 0.0020 0.10	mg/L mg/L  CU  µS/cm mg/L	2019-10-30 N/A N/A 2019-11-13 N/A 2019-11-08 2019-11-04 2019-11-04	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90	MAC = 0.1 None Required N/A AO ≤ 500 AO ≤ 15 N/A MAC = 0.2 7.0-10.5	1.0 0.00400 0.500 -5.0 1.00 5.0 2.0 0.0020 0.10	mg/L mg/L  CU µS/cm mg/L  PH units  NTU	2019-10-30 N/A N/A 2019-11-13 N/A 2019-11-08 2019-11-04 2019-11-04 2019-11-04 2019-10-30	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters Coliforms, Total	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90 0.45	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2  7.0-10.5  OG < 1	1.0 0.00400 0.500 -5.0 1.00 5.0 2.0 0.0020 0.10 0.10	mg/L mg/L  CU µS/cm mg/L  PH units  NTU	2019-10-30  N/A  N/A  2019-11-13  N/A  2019-11-08  2019-11-04  2019-11-04  2019-11-030	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90 0.45	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2  7.0-10.5  OG < 1	1.0  0.00400 0.500 -5.0 1.00  5.0 2.0 0.0020 0.10 0.10 1 200	mg/L mg/L  CU µS/cm mg/L  PH units  NTU	2019-10-30 N/A N/A 2019-11-13 N/A 2019-11-08 2019-11-04 2019-11-04 2019-11-04 2019-10-30	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters Coliforms, Total Background Colonies E. coli	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90 0.45	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2  7.0-10.5  OG < 1  MAC = 0  N/A	1.0  0.00400 0.500 -5.0 1.00  5.0 2.0 0.0020 0.10 0.10 1 200	mg/L mg/L  CU µS/cm mg/L  PH units  NTU  CFU/100 mL  CFU/100 mL	2019-10-30  N/A  N/A  2019-11-13  N/A  2019-11-08  2019-11-04  2019-11-04  2019-10-30  2019-10-30  2019-10-30	
Calculated Parameters  Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters Coliforms, Total Background Colonies	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90 0.45	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2  7.0-10.5  OG < 1  MAC = 0  N/A	1.0  0.00400 0.500 -5.0 1.00  5.0 2.0 0.0020 0.10 0.10 1 200	mg/L mg/L  CU µS/cm mg/L  PH units  NTU  CFU/100 mL  CFU/100 mL  CFU/100 mL	2019-10-30  N/A  N/A  2019-11-13  N/A  2019-11-08  2019-11-04  2019-11-04  2019-10-30  2019-10-30  2019-10-30	
Total Trihalomethanes Hardness, Total (as CaCO3) Langelier Index Solids, Total Dissolved  General Parameters Colour, True Conductivity (EC) Cyanide, Total pH Turbidity  Microbiological Parameters Coliforms, Total Background Colonies E. coli  Total Metals	0.0732 119 0.2 101 < 5.0 266 < 0.0020 7.90 0.45	MAC = 0.1  None Required  N/A  AO ≤ 500  AO ≤ 15  N/A  MAC = 0.2  7.0-10.5  OG < 1  MAC = 0  N/A  MAC = 0	1.0 0.00400 0.500 -5.0 1.00  5.0 2.0 0.0020 0.10 0.10  1 200 1	mg/L mg/L  CU µS/cm mg/L  PH units  NTU  CFU/100 mL  CFU/100 mL  CFU/100 mL	2019-10-30  N/A  N/A  2019-11-13  N/A  2019-11-08  2019-11-04  2019-11-04  2019-10-30  2019-10-30  2019-10-30	

Caring About Results, Obviously.

Page 3 of 6





**TEST RESULTS** 

REPORTED TO Peachland, Corporation of the District of PROJECT General Potability WORK ORDER N000568 REPORTED 2019-11-29 11:47

Analyte	Result	Guideline	RL	Units	Analyzed	Qualifie	
Peachland Creek - Raw (Gabion) (N000568-02)   Matrix: Water   Sampled: 2019-10-29 08:00, Continued							
Fotal Metals, Continued							
Barium, total	0.0597	MAC = 1	0.0050	mg/L	2019-11-02		
Boron, total	0.0075	MAC = 5	0.0050	mg/L	2019-11-02		
Cadmium, total	< 0.000010	MAC = 0.005	0.000010	mg/L	2019-11-02		
Calcium, total	36.8	None Required	0.20	mg/L	2019-11-02		
Chromium, total	< 0.00050	MAC = 0.05	0.00050	mg/L	2019-11-02		
Cobalt, total	< 0.00010	N/A	0.00010	mg/L	2019-11-02		
Copper, total	0.00090	MAC = 2	0.00040	mg/L	2019-11-02		
Iron, total	0.038	AO ≤ 0.3	0.010	mg/L	2019-11-02		
Lead, total	< 0.00020	MAC = 0.005	0.00020	mg/L	2019-11-02		
Magnesium, total	6.48	None Required	0.010	mg/L	2019-11-02		
Manganese, total	0.00195	MAC = 0.12	0.00020	mg/L	2019-11-02		
Mercury, total	< 0.000040	MAC = 0.001	0.000040	mg/L	2019-11-02	CT5	
Molybdenum, total	0.00687	N/A	0.00010	mg/L	2019-11-02		
Nickel, total	< 0.00040	N/A	0.00040	mg/L	2019-11-02		
Potassium, total	2.15	N/A	0.10	mg/L	2019-11-02		
Selenium, total	< 0.00050	MAC = 0.05	0.00050	mg/L	2019-11-02		
Sodium, total	11.0	AO ≤ 200	0.10	mg/L	2019-11-02		
Strontium, total	0.234	7	0.0010	mg/L	2019-11-02		
Uranium, total	0.00348	MAC = 0.02	0.000020	mg/L	2019-11-02		
Zinc, total	< 0.0040	AO ≤ 5	0.0040	mg/L	2019-11-02		
folatile Organic Compounds (VOC)							
Bromodichloromethane	0.0033	N/A	0.0010	mg/L	2019-11-08		
Bromoform	< 0.0010	N/A	0.0010		2019-11-08		
Chloroform	0.0699	N/A	0.0010		2019-11-08		
Dibromochloromethane	< 0.0010	N/A	0.0010	mg/L	2019-11-08		
Surrogate: Toluene-d8	97		70-130	%	2019-11-08		
Surrogate: 4-Bromofluorobenzene	63		70-130	%	2019-11-08	S02	

#### Sample Qualifiers:

- CT5 This sample has been incorrectly preserved for Mercury analysis
- HT1 The sample was prepared and/or analyzed past the recommended holding time.
- HT2 The 15 minute recommended holding time (from sampling to analysis) has been exceeded field analysis is recommended.
- S02 Surrogate recovery outside of control limits. Data accepted based on acceptable recovery of other surrogates.

Page 4 of 6





#### APPENDIX 1: SUPPORTING INFORMATION

REPORTED TO Peachland, Corporation of the District of PROJECT General Potability WORK ORDER REPORTED N000568 2019-11-29 11:47

Analysis Description	Method Ref.	Technique	Location
Anions in Water	SM 4110 B (2017)	Ion Chromatography	Kelowna
Coliforms, Total in Water	SM 9222 B (2017)	Membrane Filtration / m-Endo Agar	Kelowna
Colour, True in Water	SM 2120 C (2017)	Spectrophotometry (456 nm)	Kelowna
Conductivity in Water	SM 2510 B (2017)	Conductivity Meter	Kelowna
Cyanide, SAD in Water	ASTM D7511-12	Flow Injection with In-Line UV Digestion and Amperometry	Kelowna
E. coli in Water	SM 9222 G (2017)	Membrane Filtration / Nutrient Agar with MUG	Kelowna
Hardness in Water	SM 2340 B* (2017)	Calculation: 2.497 [total Ca] + 4.118 [total Mg] (Est)	N/A
Langelier Index in Water	SM 2330 B (2017)	Calculation	N/A
pH in Water	SM 4500-H+ B (2017)	Electrometry	Kelowna
Solids, Total Dissolved in Water	SM 1030 E (2017)	SM 1030 E (2011)	N/A
Total Metals in Water	EPA 200.2* / EPA 6020B	HNO3+HCl Hot Block Digestion / Inductively Coupled Plasma-Mass Spectroscopy (ICP-MS)	Richmond
Trihalomethanes in Water	EPA 5030B / EPA 8260D	Purge&Trap / GC-MSD (SIM)	Richmond
Turbidity in Water	SM 2130 B (2017)	Nephelometry	Kelowna

Note: An asterisk in the Method Reference indicates that the CARO method has been modified from the reference method

#### Glossary of Terms:

RL Reporting Limit (default)

Less than the specified Reporting Limit (RL) - the actual RL may be higher than the default RL due to various factors

Greater than the specified Result

AO Aesthetic Objective

CFU/100 mL Colony Forming Units per 100 millilitres

CU Colour Units (referenced against a platinum cobalt standard)

MAC Maximum Acceptable Concentration (health based)

mg/L Milligrams per litre

NTU Nephelometric Turbidity Units
OG Operational Guideline (treated water)
pH units pH < 7 = acidic, ph > 7 = basic
µS/cm Microsiemens per centimetre
ASTM ASTM International Test Methods

EPA United States Environmental Protection Agency Test Methods

SM Standard Methods for the Examination of Water and Wastewater, American Public Health Association





#### APPENDIX 1: SUPPORTING INFORMATION

REPORTED TO Peachland, Corporation of the District of **PROJECT** 

General Potability

WORK ORDER REPORTED

N000568 2019-11-29 11:47

#### General Comments:

The results in this report apply to the samples analyzed in accordance with the Chain of Custody document. This analytical report must be reproduced in its entirety. CARO is not responsible for any loss or damage resulting directly or indirectly from error or omission in the conduct of testing. Liability is limited to the cost of analysis. Samples will be disposed of 30 days after the test report has been issued unless otherwise agreed to in writing. The quality control (QC) data is available upon request

Results in Bold indicate values that are above CARO's method reporting limits. Any results that are above regulatory limits are highlighted red. Please note that results will only be highlighted red if the regulatory limits are included on the CARO report. Any Bold and/or highlighted results do not take into account method uncertainty. If you would like method uncertainty or regulatory limits to be included on your report, please contact your Account Manager:teamcaro@caro.ca

#### Appendix II - Trihalomethane Analyses



#### CERTIFICATE OF ANALYSIS

REPORTED TO Peachland, Corporation of the District of

5806 Beach Avenue

PEACHLAND, BC V0H 1X7

ATTENTION Shawn Grundy

PO NUMBER
PROJECT Chemistry

PROJECT INFO

WORK ORDER 9051285

RECEIVED / TEMP 2019-05-14 12:00 / 9°C REPORTED 2019-05-22 15:17 COC NUMBER No Number

#### Introduction:

CARO Analytical Services is a testing laboratory full of smart, engaged scientists driven to make the world a safer and healthier place. Through our clients' projects we become an essential element for a better world. We employ methods conducted in accordance with recognized professional standards using accepted testing methodologies and quality control efforts. CARO is accredited by the Canadian Association for Laboratories Accreditation (CALA) to ISO 17025:2005 for specific tests listed in the scope of accreditation approved by CALA.

#### Big Picture Sidekicks



We've Got Chemistry



Ahead of the Curve



You know that the sample you collected after snowshoeing to site, digging 5 meters, and racing to get it on a plane so you can submit it to the lab for time sensitive results needed to make important and expensive decisions (whew) is VERY important. We know that too.

It's simple. We figure the more you enjoy working with our fun and engaged team members; the more likely you are to give us continued opportunities to support you.

Through research, regulation knowledge, and instrumentation, we are your analytical centre for the technical knowledge you need, BEFORE you need it, so you can stay up to date and in the know.

If you have any questions or concerns, please contact me at estclair@caro.ca

Authorized By:

Eilish St.Clair, B.Sc., C.I.T. Client Service Representative

1-888-311-8846 | www.caro.ca

#110 4011 Viking Way Richmond, BC V6V 2K9 | #102 3677 Highway 97N Kelowna, BC V1X 5C3 | 17225 109 Avenue Edmonton, AB TSS 1H7





## **TEST RESULTS**

REPORTED TO	Peachland, Corporation of the District of	WORK ORDER	9051285
PROJECT	Chemistry	REPORTED	2019-05-22 15:17

Analyte	Result	Guideline	RL U	Units	Analyzed	Qualifier
#1 Todd Rd Washroom (9051285-01)   N	latrix: Water   Samp	led: 2019-05-14 08	1:00			
Calculated Parameters						
Total Trihalomethanes	0.0581	MAC = 0.1	0.00400 n	ng/L	N/A	
Volatile Organic Compounds (VOC)						
Bromodichloromethane	0.0037	N/A	0.0010 n	ng/L	2019-05-21	
Bromoform	< 0.0010	N/A	0.0010 n	ng/L	2019-05-21	
Chloroform	0.0544	N/A	0.0010 n	ng/L	2019-05-21	
Dibromochloromethane	< 0.0010	N/A	0.0010 n	ng/L	2019-05-21	
Surrogate: Toluene-d8	98		70-130 9	%	2019-05-21	
Surrogate: 4-Bromofluorobenzene	94		70-130 9	%	2019-05-21	

## #3 Swimbay Washroom (9051285-02) | Matrix: Water | Sampled: 2019-05-14 07:45

Calculated Parameters				
Total Trihalomethanes	0.173	MAC = 0.1	0.0130 mg/L	N/A
/olatile Organic Compounds (VOC)				
Bromodichloromethane	0.0045	N/A	0.0010 mg/L	2019-05-21
Bromoform	< 0.0010	N/A	0.0010 mg/L	2019-05-21
Chloroform	0.168	N/A	0.0010 mg/L	2019-05-22
Dibromochloromethane	< 0.0010	N/A	0.0010 mg/L	2019-05-21
Surrogate: Toluene-d8	115		70-130 %	2019-05-21
Surrogate: 4-Bromofluorobenzene	108		70-130 %	2019-05-21





#### APPENDIX 1: SUPPORTING INFORMATION

REPORTED TO Peachland, Corporation of the District of PROJECT PROJECT

Analysis Description	Method Ref.	Technique	Location
Trihalomethanes in Water	EPA 5030B / EPA 8260D	Purge&Trap / GC-MSD (SIM)	Richmond

#### Glossary of Terms:

RL Reporting Limit (default)

Less than the specified Reporting Limit (RL) - the actual RL may be higher than the default RL due to various factors

MAC Maximum Acceptable Concentration (health based)

mg/L Milligrams per litre

EPA United States Environmental Protection Agency Test Methods

#### Guidelines Referenced in this Report:

Guidelines for Canadian Drinking Water Quality (Health Canada, Feb 2017)

Note: In some cases, the values displayed on the report represent the lowest guideline and are to be verified by the end user


#### General Comments:

The results in this report apply to the samples analyzed in accordance with the Chain of Custody document. This analytical report must be reproduced in its entirety. CARO is not responsible for any loss or damage resulting directly or indirectly from error or omission in the conduct of testing. Liability is limited to the cost of analysis. Samples will be disposed of 30 days after the test report has been issued unless otherwise agreed to in writing. The quality control (QC) data is available upon request

Results in **Bold** indicate values that are above CARO's method reporting limits. Any results that are above regulatory limits are highlighted red. Please note that results will only be highlighted red if the regulatory limits are included on the CARO report. Any Bold and/or highlighted results do <u>not</u> take into account method uncertainty. If you would like method uncertainty or regulatory limits to be included on your report, please contact your Account Manager:estclair@caro.ca

Appendix III - 2019 Water Consumption

		Volume				
	Trepanier	Peachland	Lake			
Month	Creek	Creek	Pumps	Total	m3	ML
January	6,647,700	13,709,000		20,356,700	92,543	92.54
February	5,957,000	13,450,000		19,407,000	88,226	88.23
March	7,659,500	14,764,000		22,423,500	101,939	101.94
April	9,069,900	17,280,000		26,349,900	119,789	119.79
May	10,721,400	38,925,000	444,422	50,090,822	227,717	227.72
June	31,190,800	63,272,000		94,462,800	429,436	429.44
July	27,662,200	43,620,000		71,282,200	324,055	324.06
August	31,270,500	49,609,000		80,879,500	367,685	367.69
September	21,776,400	29,742,000		51,518,400	234,207	234.21
October	7,988,400	16,726,000		24,714,400	112,354	112.35
November	5,495,100	14,764,000		20,259,100	92,100	92.10
December	4,767,300	13,526,000		18,293,300	83,163	83.16
TOTALS	170,206,200	329,387,000	444,422	500,037,622	2,273,216	2,273.22



Peachland water use by source (percentage)

## Appendix IV – Turbidity data

	Daily Average Turbidity (NTU)				
	Peachland	Trepanier	OK Lake		
01-Jan-19	0.5	0.51	OFF		
02-Jan-19	0.54	0.52	OFF		
03-Jan-19	0.48	0.5	OFF		
04-Jan-19	0.46	0.48	OFF		
05-Jan-19	0.46	0.52	OFF		
06-Jan-19	0.48	0.51	OFF		
07-Jan-19	0.49	0.53	OFF		
08-Jan-19	0.45	0.56	OFF		
09-Jan-19	0.49	0.63	OFF		
10-Jan-19	0.51	0.55	OFF		
11-Jan-19	0.52	0.6	OFF		
12-Jan-19	0.51	0.61	OFF		
13-Jan-19	0.5	0.58	OFF		
14-Jan-19	0.5	0.59	OFF		
15-Jan-19	0.48	0.6	OFF		
16-Jan-19	0.48	0.53	OFF		
17-Jan-19	0.5	0.55	OFF		
18-Jan-19	0.54	0.66	OFF		
19-Jan-19	0.51	0.68	OFF		
20-Jan-19	0.52	N/A	OFF		
21-Jan-19	0.53	N/A	OFF		
22-Jan-19	0.5	N/A	OFF		
23-Jan-18	0.51	N/A	OFF		

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
24-Jan-19	0.49	N/A	OFF
25-Jan-19	0.5	N/A	OFF
26-Jan-19	0.51	N/A	OFF
27-Jan-19	0.48	N/A	OFF
28-Jan-19	0.47	N/A	OFF
29-Jan-19	0.48	N/A	OFF
30-Jan-19	0.46	N/A	OFF
31-Jan-19	0.48	N/A	OFF
01-Feb-19	0.50	0.32	OFF
02-Feb-19	0.54	0.41	OFF
03-Feb-19	0.48	0.35	OFF
04-Feb-19	0.46	0.41	OFF
05-Feb-19	0.46	0.32	OFF
06-Feb-19	0.45	0.33	OFF
07-Feb-19	0.55	0.36	OFF
08-Feb-19	0.46	0.48	OFF
09-Feb-19	0.46	0.49	OFF
10-Feb-19	0.46	0.55	OFF
11-Feb-19	0.46	0.64	OFF
12-Feb-19	0.49	0.56	OFF
13-Feb-19	0.45	0.53	OFF
14-Feb-19	0.44	0.51	OFF
15-Feb-19	0.55	0.48	OFF

	Daily Average Turbidity (NTU)			
	Peachland	Trepanier	OK Lake	
16-Feb-19	0.53	0.5	OFF	11-Ma
17-Feb-19	0.5	0.48	OFF	12-Ma
18-Feb-19	0.47	0.5	OFF	13-Ma
19-Feb-19	0.44	0.45	OFF	14-Ma
20-Feb-19	0.45	0.44	OFF	15-Ma
21-Feb-19	0.46	0.45	OFF	16-Ma
22-Feb-19	0.47	0.42	OFF	17-Ma
23-Feb-19	0.44	0.4	OFF	18-Ma
24-Feb-19	0.49	0.42	OFF	19-Ma
25-Feb-19	0.48	0.39	OFF	20-Ma
26-Feb-19	0.46	0.4	OFF	21-Ma
27-Feb-19	0.39	0.4	OFF	22-Ma
28-Feb-19	0.42	0.4	OFF	23-Ma
01-Mar-19	0.47	0.51	OFF	24-Ma
02-Mar-19	0.48	0.52	OFF	25-Ma
03-Mar-19	0.42	0.5	OFF	26-Ma
04-Mar-19	0.4	0.48	OFF	27-Ma
05-Mar-19	0.41	0.52	OFF	28-Ma
06-Mar-19	0.44	0.51	OFF	29-Ma
07-Mar-19	0.49	0.53	OFF	30-Ma
08-Mar-19	0.49	0.56	OFF	31-Ma
09-Mar-19	0.49	0.63	OFF	1-Apr
10-Mar-19	0.49	0.55	OFF	2-Apr

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
11-Mar-19	0.5	0.6	OFF
12-Mar-19	0.47	0.61	OFF
13-Mar-19	0.51	0.58	OFF
14-Mar-19	0.49	0.59	OFF
15-Mar-19	0.54	0.6	OFF
16-Mar-19	0.58	0.69	OFF
17-Mar-19	0.57	0.71	OFF
18-Mar-19	0.53	0.87	OFF
19-Mar-19	0.61	0.76	OFF
20-Mar-19	0.58	0.82	OFF
21-Mar-19	0.61	0.9	OFF
22-Mar-19	0.66	0.87	OFF
23-Mar-19	0.62	0.86	OFF
24-Mar-19	0.68	0.97	OFF
25-Mar-19	0.7	0.95	OFF
26-Mar-19	0.73	0.89	OFF
27-Mar-19	0.78	0.88	OFF
28-Mar-19	0.69	0.95	OFF
29-Mar-19	0.74	0.93	OFF
30-Mar-19	0.85	0.9	OFF
31-Mar-19	0.74	0.97	OFF
1-Apr-19	0.75	0.65	OFF
2-Apr-19	0.90	0.70	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
3-Apr-19	0.85	0.79	OFF
4-Apr-19	0.92	0.73	OFF
5-Apr-19	0.98	0.84	OFF
6-Apr-19	0.95	0.59	OFF
7-Apr-19	0.89	0.48	OFF
8-Apr-19	0.8	0.81	OFF
9-Apr-19	0.81	0.91	OFF
10-Apr-19	0.88	1.09	OFF
11-Apr-19	0.91	1.12	OFF
12-Apr-19	0.87	1.26	OFF
13-Apr-19	0.78	1.23	OFF
14-Apr-19	0.72	1.23	OFF
15-Apr-19	0.73	1.65	OFF
16-Apr-19	0.72	1.26	OFF
17-Apr-19	0.82	1.29	OFF
18-Apr-19	0.69	1.93	OFF
19-Apr-19	0.81	3	OFF
20-Apr-19	1.24	2.82	OFF
21-Apr-19	1.23	1.47	OFF
22-Apr-19	1.0	1.34	OFF
23-Apr-19	0.86	1.17	OFF
24-Apr-19	0.9	1.65	OFF
25-Apr-19	1.0	1.12	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
26-Apr-19	0.86	0.94	OFF
27-Apr-19	0.81	0.89	OFF
28-Apr-19	0.71	0.8	OFF
29-Apr-19	0.75	0.81	OFF
30-Apr-19	1.2	0.94	OFF
1-May-19	1.02	0.7	OFF
2-May-19	0.91	0.93	OFF
3-May-19	0.88	1.01	OFF
4-May-19	0.92	0.9	OFF
5-May-19	0.93	1.18	OFF
6-May-19	0.9	1.78	OFF
7-May-19	0.96	2.51	OFF
8-May-19	1.16	2.55	OFF
9-May-19	1.56	3.18	OFF
10-May-19	1.43	OFF	0.7
11-May-19	0.92	OFF	0.8
12-May-19	0.88	OFF	0.9
13-May-19	1.89	OFF	0.9
14-May-19	1.14	OFF	0.8
15-May-19	0.87	OFF	0.9
16-May-19	0.89	OFF	0.9
17-May-19	1.14	OFF	0.7
18-May-19	1.34	OFF	0.6

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
19-May-19	0.98	OFF	0.8
20-May-19	0.89	OFF	0.8
21-May-19	0.87	OFF	0.9
22-May-19	0.86	OFF	0.9
23-May-19	0.85	OFF	1
24-May-19	0.83	OFF	1
25-May-19	0.8	OFF	1
26-May-19	0.79	OFF	0.9
27-May-19	0.82	OFF	0.9
28-May-19	0.85	0.8	OFF
29-May-19	0.87	0.8	OFF
30-May-19	0.88	0.49	OFF
31-May-19	0.92	0.45	OFF
1-Jun-19	0.86	0.45	OFF
2-Jun-19	0.85	0.45	OFF
3-Jun-19	0.87	0.48	OFF
4-Jun-19	0.81	0.52	OFF
5-Jun-19	0.85	0.44	OFF
6-Jun-19	0.8	0.54	OFF
7-Jun-19	0.78	0.56	OFF
8-Jun-19	0.75	0.56	OFF
9-Jun-19	0.72	0.58	OFF
10-Jun-19	0.74	0.5	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
11-Jun-19	0.72	0.35	OFF
12-Jun-19	0.72	0.39	OFF
13-Jun-19	0.79	0.41	OFF
14-Jun-19	0.74	0.36	OFF
15-Jun-19	0.7	0.36	OFF
16-Jun-19	0.74	0.41	OFF
17-Jun-19	0.7	0.38	OFF
18-Jun-19	0.68	0.49	OFF
19-Jun-19	0.69	0.55	OFF
20-Jun-19	0.7	0.54	OFF
21-Jun-19	0.68	0.63	OFF
22-Jun-19	0.66	0.72	OFF
23-Jun-19	0.66	0.81	OFF
24-Jun-19	0.72	0.73	OFF
25-Jun-19	0.65	0.8	0.7
26-Jun-19	0.64	0.59	0.8
27-Jun-19	0.65	0.52	0.9
28-Jun-19	0.84	0.55	0.9
29-Jun-19	0.81	0.67	0.8
30-Jun-19	0.69	0.65	0.9
1-Jul-19	0.64	0.53	0.9
2-Jul-19	0.62	0.56	0.7
3-Jul-19	0.62	0.46	0.6

Ī	Daily Average Turbidity (NTU)		
-	Peachland	Trepanier	OK Lake
4-Jul-19	0.62	0.36	OFF
5-Jul-19	0.59	0.34	OFF
6-Jul-19	0.66	0.34	OFF
7-Jul-19	0.63	0.29	OFF
8-Jul-19	0.58	0.26	OFF
9-Jul-19	0.6	0.26	OFF
10-Jul-19	0.58	0.31	OFF
11-Jul-19	0.82	0.32	OFF
12-Jul-19	0.78	0.28	OFF
13-Jul-19	0.7	0.28	OFF
14-Jul-19	0.62	0.3	OFF
15-Jul-19	0.62	0.38	OFF
16-Jul-19	0.63	0.41	OFF
17-Jul-19	0.64	0.48	OFF
18-Jul-19	0.61	0.55	OFF
19-Jul-19	0.58	0.63	OFF
20-Jul-19	0.57	0.71	OFF
21-Jul-19	0.59	0.8	OFF
22-Jul-19	0.58	0.7	OFF
23-Jul-19	0.57	0.23	OFF
24-Jul-19	0.66	0.3	OFF
25-Jul-19	0.65	0.2	OFF
26-Jul-19	0.63	0.21	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
27-Jul-19	0.61	0.22	OFF
28-Jul-19	0.59	0.23	OFF
29-Jul-19	0.6	0.23	OFF
30-Jul-19	0.58	0.25	OFF
31-Jul-19	0.57	0.23	OFF
1-Aug-19	0.68	0.32	OFF
2-Aug-19	0.59	0.3	OFF
3-Aug-19	0.61	0.31	OFF
4-Aug-19	0.59	0.31	OFF
5-Aug-19	0.58	0.34	OFF
6-Aug-19	0.58	0.57	OFF
7-Aug-19	0.61	0.36	OFF
8-Aug-19	0.6	0.18	OFF
9-Aug-19	0.59	0.16	OFF
10-Aug-19	0.63	0.18	OFF
11-Aug-19	0.61	0.15	OFF
12-Aug-19	0.61	0.22	OFF
13-Aug-19	0.64	0.25	OFF
14-Aug-19	0.65	0.21	OFF
15-Aug-19	0.66	0.19	OFF
16-Aug-19	0.67	0.2	OFF
17-Aug-19	0.63	0.23	OFF
18-Aug-19	0.65	0.28	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
19-Aug-19	0.69	0.37	OFF
20-Aug-19	0.6	0.28	OFF
21-Aug-19	0.72	0.39	OFF
22-Aug-19	0.64	0.15	OFF
23-Aug-19	0.67	0.15	OFF
24-Aug-19	0.61	0.13	OFF
25-Aug-19	0.73	0.15	OFF
26-Aug-19	0.7	0.16	OFF
27-Aug-19	0.77	0.15	OFF
28-Aug-19	0.74	0.17	OFF
29-Aug-19	0.65	0.17	OFF
30-Aug-19	0.66	0.17	OFF
31-Aug-19	0.75	0.22	OFF
1-Sep-19	0.73	0.23	OFF
2-Sep-19	0.84	0.27	OFF
3-Sep-19	0.75	0.26	OFF
4-Sep-19	0.77	0.18	OFF
5-Sep-19	0.76	0.18	OFF
6-Sep-19	0.68	0.17	OFF
7-Sep-19	0.71	0.17	OFF
8-Sep-19	0.8	0.18	OFF
9-Sep-19	0.82	0.16	OFF
10-Sep-19	0.84	0.21	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
11-Sep-19	0.77	0.17	OFF
12-Sep-19	0.87	0.16	OFF
13-Sep-19	0.8	0.17	OFF
14-Sep-19	0.8	0.17	OFF
15-Sep-19	0.9	0.19	OFF
16-Sep-19	0.91	0.22	OFF
17-Sep-19	0.83	0.21	OFF
18-Sep-19	0.81	0.2	OFF
19-Sep-19	0.9	0.23	OFF
20-Sep-19	0.87	0.2	OFF
21-Sep-19	0.85	0.2	OFF
22-Sep-19	0.84	0.19	OFF
23-Sep-19	0.81	0.19	OFF
24-Sep-19	0.83	0.19	OFF
25-Sep-19	0.8	0.2	OFF
26-Sep-19	0.84	0.19	OFF
27-Sep-19	0.83	0.18	OFF
28-Sep-19	0.85	0.18	OFF
29-Sep-19	0.88	0.2	OFF
30-Sep-19	0.87	0.17	OFF
1-Oct-19	0.87	0.16	OFF
2-Oct-19	0.88	0.21	OFF
3-Oct-19	0.78	0.17	OFF

	Daily Avera	age Turbidity	(NTU)
	Peachland	Trepanier	OK Lake
4-Oct-19	0.72	0.16	OFF
5-Oct-19	0.7	0.14	OFF
6-Oct-19	0.7	0.14	OFF
7-Oct-19	0.74	0.2	OFF
8-Oct-19	0.77	0.19	OFF
9-Oct-19	0.8	0.21	OFF
10-Oct-19	0.82	0.25	OFF
11-Oct-19	0.83	0.19	OFF
12-Oct-19	0.81	0.26	OFF
13-Oct-19	0.77	0.45	OFF
14-Oct-19	0.89	0.81	OFF
15-Oct-19	0.85	0.74	OFF
16-Oct-19	0.88	0.77	OFF
17-Oct-19	0.87	0.89	OFF
18-Oct-19	0.73	0.89	OFF
19-Oct-19	0.66	0.75	OFF
20-Oct-19	0.67	0.76	OFF
21-Oct-19	0.7	0.81	OFF
22-Oct-19	0.72	0.7	OFF
23-Oct-19	0.85	0.78	OFF
24-Oct-19	0.83	0.72	OFF
25-Oct-19	0.78	0.71	OFF
26-Oct-19	0.75	0.72	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
27-Oct-19	0.73	0.82	OFF
28-Oct-19	0.72	0.81	OFF
29-Oct-19	0.76	0.88	OFF
30-Oct-19	0.6	0.8	OFF
31-Oct-19	0.62	0.71	OFF
1-Nov-19	0.6	0.86	OFF
2-Nov-19	0.61	0.76	OFF
3-Nov-19	0.62	0.88	OFF
4-Nov-19	0.59	0.83	OFF
5-Nov-19	0.58	0.84	OFF
6-Nov-19	0.56	0.85	OFF
7-Nov-19	0.57	0.83	OFF
8-Nov-19	0.56	0.87	OFF
9-Nov-19	0.55	0.86	OFF
10-Nov-19	0.55	0.84	OFF
11-Nov-19	0.56	0.87	OFF
12-Nov-19	0.56	0.93	OFF
13-Nov-19	0.58	0.86	OFF
14-Nov-19	0.61	0.61	OFF
15-Nov-19	0.64	0.21	OFF
16-Nov-19	0.7	0.24	OFF
17-Nov-19	0.67	0.23	OFF
18-Nov-19	0.73	0.23	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
19-Nov-19	0.74	0.17	OFF
20-Nov-19	0.75	0.15	OFF
21-Nov-19	0.7	0.18	OFF
22-Nov-19	0.76	0.18	OFF
23-Nov-19	0.8	0.15	OFF
24-Nov-19	0.86	0.12	OFF
25-Nov-19	0.86	0.15	OFF
26-Nov-19	0.79	0.16	OFF
27-Nov-19	0.66	0.14	OFF
28-Nov-19	0.62	0.11	OFF
29-Nov-19	0.58	0.11	OFF
30-Nov-19	0.55	0.11	OFF
1-Dec-19	0.63	0.11	OFF
2-Dec-19	0.9	0.15	OFF
3-Dec-19	0.99	0.17	OFF
4-Dec-19	0.65	0.15	OFF
5-Dec-19	0.62	0.14	OFF
6-Dec-19	0.64	0.13	OFF
7-Dec-19	0.6	0.13	OFF
8-Dec-19	0.56	0.13	OFF
9-Dec-19	0.57	0.13	OFF
10-Dec-19	0.56	0.14	OFF
11-Dec-19	0.59	0.11	OFF

	Daily Average Turbidity (NTU)		
	Peachland	Trepanier	OK Lake
12-Dec-19	0.59	0.11	OFF
13-Dec-19	0.62	0.14	OFF
14-Dec-19	0.6	0.14	OFF
15-Dec-19	0.58	0.14	OFF
16-Dec-19	0.54	0.14	OFF
17-Dec-19	0.55	0.12	OFF
18-Dec-19	0.6	0.16	OFF
19-Dec-19	0.55	0.13	OFF
20-Dec-19	0.61	0.17	OFF
21-Dec-19	0.6	0.17	OFF
22-Dec-19	0.59	0.15	OFF
23-Dec-19	0.63	0.14	OFF
24-Dec-19	0.59	0.16	OFF
25-Dec-19	0.59	0.13	OFF
26-Dec-19	0.6	0.11	OFF
27-Dec-19	0.58	0.12	OFF
28-Dec-19	0.62	0.14	OFF
29-Dec-19	0.62	0.14	OFF
30-Dec-19	0.69	0.14	OFF
31-Dec-19	0.83	0.12	OFF